



Roman blinds are a traditional and yet contemporary window treatment. With an extensive range of fabrics and with three design options to choose from, the Roman Blind can enhance many décor styles. The Roman Blind can be made using Lightfilter or Blockout fabrics, enabling it to suit all light and privacy requirements.

CLASSIC ROMAN

The Classic Roman Blind is manufactured by sewing a small pocket on the back of the blind. A slim, round fibreglass rod is inserted into the pocket. The cords to enable lifting of the blind are attached via a P.V.C ring that is clipped on to the pocket, creating the Roman folding action. Due to the pockets being sewn in the Classic Roman, needle holes which will allow light to come through may be visible in some fabrics, particularly Blockouts. The Classic Roman is a light weight blind which assists in ease of operation. The simplicity of the Classic Roman Blind allows it to sit comfortably in any décor style. The Classic Roman is available in all options of operation – cord lock and chain control.

SEWLESS ROMAN

(aluminium back extrusion)

The Sewless Roman Blind is manufactured using aluminium extrusion on the back of the blind into which the fabric is splined (tucked). This creates a fine tuck line on the front of the blind. The extrusion is not visible from the front of the blind which means this style of Roman provides an elegant and simple appearance. The cords to enable lifting of the blind are attached via a P.V.C ring clipped to the extrusion, creating the Roman folding action. A feature of the Sewless Roman is that there is no need for sewing, which eliminates the needle holes that may allow light to show through Blockout fabrics. The Sewless Roman Blind is available in all options of operation – cord lock and chain control.

PLANTATION ROMAN

(timber battens)

The Plantation Roman Blind is accessorised with timber battens attached to both the front and back of the blind. The battens are available in a wide range of painted or stained finishes to enhance the fabric colour and will be supplied in the same colour on the front and back. The profile of the front batten is half round and the profile of the back batten is flat. The battens are secured to the fabric with a small staple through the back batten which also secures the front batten. The cords to enable lifting of the blind are attached to the back batten via a small metal eyelet, creating the Roman folding action. A 50mm timber valance is attached to the top of the blind. A feature of the Plantation Roman is that there is no need for sewing, eliminating the needle holes that allow light to show through Blockout fabrics. The Plantation Roman Blind is available in all options of operation – cord lock and chain control.

Roman Blind Operation Options

CORDLOCK OPERATION

Head rail	Brackets	Projection of bracket to the front of the blind	Cord Colours	Maximum Size	Minimum Width	Maximum Width	Maximum Drop
Aluminium-Brushed Silver (21mm x 10mm)	White Acrylic for Inside and Outside Mount * 75mm Extension Bracket Available upon request	Outside Mount 40mm Inside Mount 40mm	White, Black	4.5m ²	360mm	2410mm	3000mm

CHAIN CONTROL OPERATION

Head rail	Brackets	Projection of bracket to the front of the blind	Chain Colours	Maximum Size	Minimum Width	Maximum Width	Maximum Drop
White Powder Coated Aluminium (35mm deep x 30mm wide)	White Powder Coated Steel	Outside Mount 44mm Inside Mount 44mm	White, Black, Ivory, Grey	6m ²	360mm	2410mm	3000mm

The Plantation Roman B blind is accessorised with timber battens attached to both the front and back of the blind. The battens are available in a wide range of painted or stained finishes to enhance the fabric colour and will be supplied the same colour on the front and back. The profile of the front batten is half round and the profile of the back batten is flat. The battens are secured to the fabric with a small staple through the back batten which also secures the front batten.



Black



Brown



Cherry



Baltic



Teak



Natural



Albaster



White

TIMBER BATTENS – (for Plantation style)

Colours available - White, Alabaster, Black, Brown, Cherry, Baltic, Natural, Teak
 Front of Blind – half round profile (12mm wide x 8mm deep).
 Back of Blind - flat profile (12mm wide x 5mm deep).

ALUMINIUM BACK EXTRUSION – (for Sewless style)

Colour – Beige

OVERLOCKING

Some fabrics will automatically be overlocked as per the 'Fabric List'

BASE OF BLIND

Classic – 30mm sewn pocket with P.V.Clathe
 Sewless- 30mm sewn pocket with P.V.Clathe
 Plantation- timber battens back and front

TASSEL (Acorn) -

White, Alabaster, Black, Teak, Baltic, Redwood, Cherry, Rosewood, Mocha
 The tassel colour will be co-ordinated to suit the battens and/or the back colour of the fabric.

POCKET SPACING AND LINING UP

The distance between each pocket will vary depending on the drop of the Blind and the operation system. The approximate distance is 250 to 380. The first spacing from the top of the blind will differ between each operation style.

It can not be guaranteed that the pocket spacing will match on Blinds with different operation and/or drops. For example there is a difference in the top pocket spacing between the cordlock and chain operation.

FACTORY STANDARD DEDUCTIONS

INSIDE MOUNT WIDTH DEDUCTION	10mm
INSIDE MOUNT DROP DEDUCTION	5mm

STACKING

Roman Blinds when fully drawn up will stack up to an approximate depth of between 300mm and 450mm. This will vary due to the drop length, blind style and operation methods.

Different drop lengths will impact on the size of the blind stack.

FABRIC (SKIN) ATTACHMENT METHOD

In all styles of Roman Blinds the fabric (skin) is attached to the head rail with Velcro.

SETTLING OUT

Roman Blinds require some time to settle out. The type of fabric used, size and weight and the style of the Blind will impact on the degree of settling. The Classic and Plantation styles are subject to minimal settling. The Sewless style will require a little longer for the fabric to settle. A Roman Blind may appear short in its drop on initial installation, however over a short period of time the fabric will settle and sit at the correct drop length. Environmental conditions can also impact on the settling out process.

FABRIC APPEARANCE

Sewless and Classic styles will sometimes show a very slight puckering of the fabric. This is unavoidable due to the tension placed on the fabric in the manufacturing process.

CHILD SAFETY

Warning stickers and mechanism are supplied at no extra charge.