

# Lifeloc

Professional Breath Alcohol Tester

The Lifeloc FC5 Hornet™ tests for the presence of alcohol without the need for mouthpieces or special attachments.

Three testing modes ensure full user control: Pass/Fail, High/Low Levels and Open Container.

Economical, rugged and easy to use the FC5 Hornet is designed and ideally suited for workplace testing, probation, parole and law enforcement.

The FC5 has an extra large fuel cell ensuring speed, accuracy and longevity.



## Lifeloc FC5 HORNET

Professional Breath Alcohol Tester

Simple, Effective, Accurate Alcohol Testing

## EASE OF USE

- 3 Testing Modes:
  - **POS +/- -NEG Mode** for rapid high volume testing.
  - **Levels Mode** for more precise sampling.
  - **Open Container Mode** for drinks and spills.
- LCD display with prompts and visual alerts:
  - Easy to interpret icons.
  - Battery level indicator.
  - Automatic backlight for Day/Night visibility.
- Audible alerts for test status.

## PRECISION INSTRUMENT

- Full sized 1 inch (2.54cm) platinum fuel cell:
  - Superior accuracy and long life.
  - Alcohol specific.
  - Twice the surface area of competitors.
- Fast response and recovery time:
  - Immediate recovery on negative.
  - <30 seconds on positive.
- Wide operating temperature range.:
  - 0-55°C or 32-130°F.


## MARKET FOCUSED

- Appropriately designed for safety sensitive workplace testing environments.
- Rugged Design:
  - Full protective rubber grip.
  - Stands up to vibrations and drops.
  - Port covers protect from dust, water and debris.
  - Easy to carry or conceal.
  - Comes in a protective carrying case.
  - Result hidden from subject for operator safety.
- Meets International Electrotechnical Commission standards:
  - Drop: IEC 68-2-32.
  - Shock: IEC 68-2-27 and IEC 68-2-29.
  - Vibration: IEC 68-2-6.

## FIVE STAR CUSTOMER CARE

- Calibration Service:
  - Fully equipped laboratory.
  - 24 hour turnaround.
  - Calibration certificate included.
  - Customer asset management.

## SCREEN SHOTS



## TEST MODES

### POS +/- -NEG MODE

- Auto tests when enough sample volume detected.
- Manual override
- Instant **+POS or -NEG** result.

### LEVELS MODE

- Alerts operator to one of three levels of alcohol:
  - Zero: <.010 %BAC
  - Low: .011-.020 %BAC
  - High: >.021 %BAC

### OPEN CONTAINER MODE

- Samples air-space over open containers.
- One button sample.
- Double pump action ensures proper test sample.
- No attachments required.



Distributed in Australia by CMM Technology™

Unit 12/3 King Edward Road, Osborne Park. Western Australia 6017

Tel: 1300 79 70 30

email: sales@cmm.com.au

web: www.cmm.com.au